

Block Connectors 930

Connection:	external 1 x 0.5 - 2.5 mm ² solid 1 x 0.5 - 1.5 mm ² solid release by release key resp. screw driver internal 1 x 0.5 - 2.5 mm ² solid 1 x 0.5 - 1.5 mm ² solid release by release key resp. screw driver capacitor 0.5 - 0.75 mm ² solid
Fixing:	by screw or rivet size Ø 2.9 - 3.0 mm or, by catch pin RS 930 (order no. 190301) into hole size Ø 3.2 mm for plates of 0.5 - 1.2 mm thickness
Stripping length:	8 mm (0.5 - 1.0 mm ²), 9 mm (1.5 - 2.5 mm ²), 9 mm (capacitor)
Important approvals:	VDE, UL
Accessories:	strain reliefs (page 86)
Upon request:	7 - 11 pole, PE contact pre-assembled, catch pins for quick fixing, printing

Description	Item	Order Number	PU
with two release keys			
1 pole	930-02/ 1	112401	2500
2 pole	930-02/ 2	112402	1000
3 pole	930-02/ 3	112403	1000
4 pole	930-02/ 4	112404	500
5 pole	930-02/ 5	112405	500
6 pole	930-02/ 6	112406	400
12 pole	930-02/12	112412	30
without release key			
1 pole	930-00/ 1	112001	2500
2 pole	930-00/ 2	112002	1000
3 pole	930-00/ 3	112003	1000
4 pole	930-00/ 4	112004	500
5 pole	930-00/ 5	112005	500
6 pole	930-00/ 6	112006	400
12 pole	930-00/12	112012	40

